



FEATURES

- Support Intel® Celeron® J1900 Series Processor
- 1 x 204-pin DDR3L 1333 SODIMM up to 4GB
- 2 x Intel GbE Controller(Wake-on-LAN & PXE support)
- 2 x SATA
- 3 x Display interface, 1 x HDMI, 1 x VGA, 1 x LVDS
- 4 x COM port for RS-232/422/485
- 1 x USB3.0, 5 x USB2.0
- 1 x 8-bit GPIO
- 1 x MicroSD slot
- 2 x Full size mini PCIe GEN2 slot with SIM slot
- Watchdog timer 0~255 steps H/W reset
- TPM1.2 supported (Optional)

SPECIFICATIONS

System

Processor	Intel® Celeron® Processor J1900 (2.0GHZ/4C/10W)
System Memory	1 x 204-pin DDR3L SODIMM sockets Non-ECC/unbuffered Data transfer rates up to 1333MT/s Memory size up to 4GB
BIOS	AMI uEFI 8MB SPI flash
Graphics	Intel 7 th generation graphics and media encode/decode engine
Audio	Realtek ALC886
Ethernet	2 x Intel I210IT GbE Controller
Watchdog Timer	H/W Reset, 0 – 255 steps Step = 1 sec. or 1 min
H/W Monitor	Voltages monitoring Temperature monitoring Smart fan supported
TPM	TPM1.2 supported (Optional)

Mechanical & Environmental

Dimension	146mm x 102mm
Power Input	DC +12V input
Power Management	ACPI 5.0 compliant
Operating Temp.	-20°C ~ 70°C
Storage Temp.	-40°C ~ 85°C
Operating Humidity	10% ~ 90% relative humidity, non-condensing

I/O

Internal I/O	1 x 2-ch 24bit LVDS	1 x 8-bit GPIO
	1 x SATA 2.0	1 x PS/2 keyboard mouse
	3 x RS-232/422/485	1 x microSD card socket
	4 x USB 2.0	1 x SIM card socket
	1 x Line-In, Line Out & Mic-In	1 x FAN connector

Rear I/O	1 x HDMI 1 x VGA 1 x RS-232/422/485 1 x USB 3.0 1 x USB 2.0 2 x GbE
Expansion	2 x Full size mini PCIe slot
Storage Temp.	-40°C ~ 85°C, 95% (non-condensing), Non-operating
Relative Humidity	10% ~ 90% relative humidity, non-condensing

ORDERING INFORMATION

Packing List

- 1 x COM port cable
- 1 x PS/2 cable
- 1 x SATA cable
- 1 x Power cable
- 1 x Driver DVD

Ordering Information

MODEL NO.	DESCRIPTION
CT-DBT01-J1900	w/ Intel® Celeron® Processor J1900 (2.0GHZ/10W)

* All specifications and photos are subject to change without notice.