

VCO-6131E-4M2

Superior AI Edge Computing System with LGA-1151 socket for Intel® CFL-R S Processor




SPECIFICATIONS

System	
Processor	Support 8 th /9 th Gen Intel® CFL-R S Processor (LGA 1151, 65W/35W TDP) <ul style="list-style-type: none"> - Intel® Core™ i7-9700E, 8 Cores, 12MB cache, up to 4.4 GHz - Intel® Core™ i5-9500E, 6 Cores, 9MB Cache, up to 4.2 GHz - Intel® Core™ i3-9100E, 4 Core, 6MB Cache, 3.7 GHz - Intel® Core™ i7-9700TE, 8 Cores, 12MB cache, up to 3.8 GHz - Intel® Core™ i5-9500TE, 6 Cores, 9MB Cache, up to 3.6 GHz - Intel® Core™ i3-9100TE, 4 Core, 6MB Cache, 3.2 GHz - Intel® Core™ i7-8700T, 6 Cores, 12MB cache, up to 4.0 GHz - Intel® Core™ i5-8500T, 6 Cores, 9MB Cache, up to 3.5 GHz - Intel® Core™ i3-8100T, 4 Cores, 6MB Cache, 3.1 GHz - Intel® Pentium® G5400T, 2 Cores, 4MB Cache, up to 3.1 GHz - Intel® Celeron® G4900T, 2 Cores, 2MB Cache, up to 2.9 GHz
System Chipset	Intel® Q370 Express Chipset
LAN Chipset	GbE1: Intel® I219LM (Support Wake-on-LAN and PXE) GbE2: Intel® I210-AT (Support Wake-on-LAN and PXE)
Audio Codec	Realtek ALC888S
System Memory	2x 260-Pin DDR4 2400/2666MHz SODIMM. Max. up to 64GB (Un-buffered and Non-ECC)
BIOS	AMI 256Mbit SPI BIOS
Watchdog	Software Programmable Supports 1~255 sec. System Reset
TPM	TPM 2.0
Display	
VGA	Yes (by optional split cable)
DVI	1x DVI-I, support resolution 1920 x 1200
DisplayPort	2x DisplayPort, support resolution 4096 x 2304
Multiple Display	Triple Display
Storage	
SSD/HDD	2x Internal 2.5" SATA HDD Bay (support H=9mm) 2x Removable 2.5" SATA HDD Bay (support H=9mm, hot-swappable) Support RAID 0, 1, 5, 10
mSATA	1x mSATA (Shared by 1x Mini PCI Express)
M.2	1x M.2 (M Key, PCIe x4, 2280, Support NVMe), 1x M.2 (E Key, PCIe x2, 2230, USB 2.0, Support CNVi)
NVMe	4x M.2 PCIe x2, 2280 (hot-swappable)
SIM Socket	2x Internal SIM socket
Expansion	
Mini PCI Express	2x Full-size Mini PCIe (1x shared by 1x mSATA)
PCI Express	1x PCIe x4 (1-lane) 1x PCIe x16 (8-lane) for GPU card 1x Slimline (8-lane) for 4x M.2 PCIe x2
Card Dimension	312mm(L) x 112mm(H)
I/O	
COM	2x RS-232/422/485 2x RS-232/422/485 (internal)
USB	4x USB 3.2 Gen 2 (10 Gbps), 5x USB 3.2 Gen 1 (5 Gbps, internal), 1x USB 3.0 header (internal)
LAN	2x RJ45
DIO	8 in / 8 out (Isolated)
Universal I/O Bracket	2x Universal I/O Bracket (By mini PCIe interface)
Others	4x WiFi Antenna Holes 1x Power Switch, 1x AT/ATX Switch, 1x Remote Power On/Off 1x PC/Car Mode Switch, 1x Delay Time Switch 1x Removable CMOS Battery (internal)
Operating System	
Windows	Windows 10
Linux	Linux kernel 5.X
Power	
Power Mode	AT, ATX
Power Supply Voltage	9~48VDC
Power Ignition Sensing	Power Ignition Management
Power Connector	3-pin Terminal Block ; 4-pin Terminal Block
Power Adaptor	Optional AC/DC 24V, 220W/280W Optional AC/DC 24V, 280W for GPU
Power Protection	OVP (Over Voltage Protection) OCP (Over Current Protection) Reverse proteceion
Environment	
Operating Temp.	-25°C to 60°C (65W / 35W CPU)
Storage Temp.	-30°C to 85°C
Relative Humidity	10% to 95% (non-condensing)
Vibration	With SSD: 3 Grms, 5 - 500 Hz, 0.5 hr/axis With HDD: 1 Grms, 5 - 500 Hz, 0.5 hr/axis
Shock	With SSD: 20G, half sine, 11ms
Standards / Certification	CE, FCC Class A
Physical	
Construction	Extruded Aluminum with Heavy Duty Metal
Dimension	157 (W) x 340 (D) x 240 (H) mm
Weight	9.5 kg
Mounting	Wall Mounting


* For 8th/9th CPUs configured to run at 65W, operating temperatures will be limited to 60°C.
** 65W CPUs may experience thermal throttling depending on extreme application workloads; this is also due to an increase in the physical CPU cores from the Intel silicon (up to 8 cores). Please note, this does not indicate system malfunction or problems in the fanless design. Please consult our embedded engineers for the best configuration to match your application requirements.
*** All specifications and photos are subject to change without notice.

EXTERNAL I/O MECHANICAL LAYOUT



DIMENSION

Unit: mm



ORDERING INFORMATION

MODEL NO.	DESCRIPTION
1-E09A22801	Adapter AC/DC 24V/11.67A 280W with 3-pin Terminal Block Plug 5.0mm Pitch
1-E09A22102	Adapter AC/DC 24V 9.2A 220W with 3-pin Terminal Block Plug 5.0mm Pitch
SFICBL022	Power Cord, 3-pin US Type, 180cm
1-TPCD00002	Power Cord, European Type, 180cm
1-TPCD00001	Power Cord, 3-pin UK Type, 180cm

PACKING LIST

- 1x VCO-6100 Series Embedded System
- 1x Utility DVD Driver
- 1x Wall Mount Kit
- 1x Accessory Kit

AVAILABLE MODELS

MODEL NO.	DESCRIPTION
VCO-6131E-4M2	Superior AI Edge Computing System with LGA-1151 socket for Intel® CFL-R S Processor