



#### Features

- 19" TFT SXGA 4:3 LCD with resistive 5-wire / projected capacitive touch
- -10°C to 50°C extended operating temperature
- Designed with aluminum die-casting front frame
- IP65 compliant front panel
- Two 10W internal speakers built-in
- Multi-language OSD built-in

#### Specifications

Display	
IP Rating	IP65
LCD Size	19" (4:3)
Max. Resolution	1280 x 1024 (SXGA)
Brightness (cd/m <sup>2</sup> )	350 / 1000 (optional)
Contrast Ratio	1000:1
LCD Color	16.7M
Pixel Pitch (mm)	0.294(H) x 0.294(V)
Viewing Angle	170/160
Backlight MTBF	50000 hrs (LED Backlight)
Touch	
Projected Capacitive	VIO-219C
Resistive 5-Wire	VIO-219R
Others Features	
Speaker	AMP 10W + 10W
OSD	LCD On/Off, Auto, Menu, Up and Down Multi-language
Operating Temperature	-10 °C ~ 50 °C
Storage Temperature	-20 °C to 60 °C
Relative Humidity	10% ~ 80% (non-condensing)
IP Level	IP 65 Compliant Front Panel
Physical	
Dimensions	450 (W) x 375 (D) x 51 (H) mm
Weights	6.07 ~ 6.20 kg
Mounting Options	VESA Mounting Holes 75 x 75mm, 100 x 100mm

#### Available Models

- VIO-219R  
19" 4:3 SXGA Resistive Touch Thin Frame Display Monitor with 2x 10W Speaker
- VIO-219C  
19" 4:3 SXGA Capacitive Touch Thin Frame Display Monitor with 2x 10W Speaker

#### Optional Accessories

- 1-E09A06008  
Adapter AC/DC 12V 5A 60W with 3pin Terminal Block Plug 5.0mm Pitch
- SFICBL022  
Power Cord, 3-pin US Type, 180cm
- 1-TPCD00002  
Power Cord, European Type
- 1-TPCD00001  
Power Cord, 3-pin UK Type, 180cm

#### Packing List

- 1x VIO-219 Display Module
- 14x Panel Mount Kit

\* All specifications and photos are subject to change without notice.

Dimension

Unit: mm

